

## Specifications

	<b>Turntable Section</b>
Type	Direct Drive
Motor	Brushless DC motor
Turntable Speeds	33-1/3, 45 and 78 rpm
Pitch Adjustment Range	±8% and ±16%
Starting Torque	2.2 kg
Build-up Characteristics	0.7 s. from standstill to 33- 1/3 rpm
Braking system	Electronic brake
Wow and Flutter	0.025% W.R.M.S.
Turntable Platter	Aluminum die-cast Diameter: 332mm Weight: Approx. 2.5kg (Including rubber sheet)

	<b>Tonearm Section</b>
Type	Static Balance
Effective Length	230mm
Overhang	15mm
Tracking Error Angle	Within 2° 32' (at the outer groove of 30cm(12") record) Within 0° 32' (at the inner groove of 30cm(12") record)
Offset Angle	22°
Arm Height Adjustment Range	0 - 6mm
Stylus Pressure Adjustment Range	0 - 4g (Direct Reading)
Head Shell Weight	Approx. 7.6g (without auxiliary weight) 5.6 - 12.0g 3.1 - 9.5g (using cartridge spacer)
Applicable Cartridge Weight Range	14.3 - 20.7g (including head shell) (with auxiliary weight) 10.0 - 16.4g 7.5 - 13.9g (using cartridge spacer) 18.7 - 25.1g (including head shell)
Cartridge Mounting Dimension	12.7 mm (1/2") interval
Head Shell Terminal Lug	1.2mmφ 4-pin terminal lug

### Terminals

Audio Output	PHONO (Pin Jack) x 1 EARTH TERMINAL x 1
--------------	--

### General

Power Supply	AC220-240 V, 50/60 Hz
Power Consumption	11 W (ON) 0.3 W (OFF)
Dimensions (W x H x D)	453 x 173 x 372 mm

### **Turntable Section**

Weight

Approx. 11.5kg

Operating temperature range

0° to +40°

Weight

35% to 80% RH (no condensation)

Accessories

Turntable, Turntable sheet, Dust cover, EP record adaptor, Balance weight, Auxiliary weight, Cartridge spacer Head shell, Overhang gauge, Screw set for cartridge, PHONO cable, PHONO earth lead, AC power supply cord, Owner's Manual