fact[®]8

Ultimate purity and elegance from the **fact** range



fact:8 in Rich walnut

The definition of fact - noun - a thing known to be true with complete certainty

PMC's vast knowledge of acoustic engineering gained from developing the world's leading professional loudspeakers has been distilled into the **fact** range. Only this level of understanding of the creative process, room acoustics and supreme engineering make **fact** possible.

With the phenomenal benefits of PMC's **A7L**™ technology the **fact** 8 floor-standing model produces the commanding power and scale that is capable of filling both medium and larger rooms with awe-inspiring dynamic sound.

With its compliment of twin **fact** bass drivers and ultra high resolution **fact** tweeter, they project an all encompassing, vivid sonic picture that can be experienced by all.

These cutting edge precision drivers are seamlessly integrated with a highly sophisticated 24dB per octave crossover network

and, in combination with the ultimately inert **ATL™** (Advanced Transmission Line) cabinet, create an entirely natural and refined balance where vocals hang in space and are truly tangible.









"This is an excellent speaker"



"They do everything well" **Highly Recommended**



"A truly great design"



fact

000 **PMC**

Textured fabric meets exotic veneers. Hidden magnets fasten the grille, further enhancing the seamless appearance



Luxury, hand polished ingot feet with reversible spike or ball tips

Take control

HF +1, 0, -1 **LF** 0, -1, -2

Audiophile grade switches provide fine-tuning, ensuring the perfect sound balance in any room, and with any source combination



With absolute transparency of audio in mind the **fact Ag** pure silver coated binding post is the solution

"Make no mistake, this speaker is the real deal!"



"Exceptional and highly desirable in every way" April 2010



"More than mere hi-fi, fact's is a great loudspeaker"





Front With grille



Rear



Freq response	28Hz – 30kHz
Sensitivity	89dB 1w 1m
Effective ATL™	
(Advanced Transmission Line Length)	3m 9.8ft
Impedance	8 Ohms
Recommended amplifier power	40 – 300W
Drive Units	LF 2 x fact 140mm/5 1/2" precision drivers
	HF fact 19mm high res SONOMEX [™] soft dome ferrofluid cooled, with 34mm surround and fact dispersion grille
Crossover Freq	1.7 kHz
Crossover type	Precision 24dB filters
Input connectors	2 pairs 4mm PMC Ag terminals (Bi-wire or Bi-amp)
Dimensions	H 1030mm + 25mm spikes



Weiaht

White silk



Rich walnut



W 155mm + 80mm ingot feet D 380mm + 23mm Ag terminal

20.0 kg 44lbs

Graphite poplar



olar Tiger ebony



subject to change without notice

PMC HOLME COURT BIGGLESWADE SG18 9ST UK T +44 (0)870 4441044 F +44 (0)870 4441045 sales@pmc-speakers.com www.pmc-speakers.com