



**AVAILABLE AT
DIGITAL CINEMA**



Technical features	Nautilus tube loaded Decoupled Double Dome aluminium tweeter Kevlar® brand fibre cone FST™ midrange Flowport™
Description	3-way vented-box system
Drive units	1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency 1x ø130mm (5 in) woven Kevlar cone FST midrange 2x ø130mm (5 in) paper/Kevlar cone bass
Frequency range	-6dB at 43Hz and 50kHz
Frequency response	48Hz - 28kHz ±3dB
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	88dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 300Hz - 20kHz
Nominal impedance	8Ω (minimum 3.0Ω)
Crossover frequency	350Hz, 4kHz
Recommended amplifier power	30W - 150W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 924mm (36.4 in) cabinet only Width: 165mm (6.5 in) cabinet only 252mm (9.9 in) including plinth Depth: 277mm (10.9 in) cabinet, grille and terminals only 298mm (11.7 in) including plinth
Net weight	19.5kg (43 lb)
Finishes	Cabinet: Grille: Rosnut Black Gloss Black Black Satin White Grey